



LEDrofit



Ditch the fluorescent bulbs and go for a greener, longer lasting lighting solution from Allanson!



Features:

- **Quick and easy replacement of T12 Fluorescent lamps**
- Insulated adaptor mounts directly into the existing lamp sockets
- Sleek clean finish with aluminum based structure that allows for continuous heat dissipation
- Diamond shape sturdy housing allows for a wider beam, angled for even and balanced illumination, eliminating hot spots
- True retrofit – mounts minimum 6" from sign face and is spaced at 12" centers
- Bright white LED in daylight color
- Operating temperature: -40°C to +50°C
- Safe 12V system
- IP 67 rating
- 5 year warranty

6000K Cool White Double-Sided LED Lamp

Part #	Lumens SS / DS	Watts SS / DS
ALLALDF18CWDS / SS	320 / 636	3.5 / 7.0
ALLALDF24CWDS / SS	534 / 1060	5.9 / 11.7
ALLALDF30CWDS / SS	641 / 1271	7.1 / 13.9
ALLALDF36CWDS / SS	855 / 1695	9.3 / 18.1
ALLALDF42CWDS / SS	961 / 1907	10.5 / 20.4
ALLALDF48CWDS / SS	1175 / 2331	12.7 / 24.6
ALLALDF60CWDS / SS	1495 / 2967	16.0 / 30.7
ALLALDF64CWDS / SS	1602 / 3179	16.7 / 31.9
ALLALDF72CWDS / SS	1816 / 3602	18.8 / 36.0
ALLALDF84CWDS / SS	2136 / 4238	21.6 / 41.0
ALLALDF96CWDS / SS	2457 / 4874	23.6 / 45.5
ALLALDF108CWDS / SS	2777 / 5510	26.3 / 49.1
ALLALDF117CWDS / SS	2991 / 5933	27.4 / 51.0
ALLALDF120CWDS / SS	3098 / 6145	29.5 / 55.8

Part numbers that end in DS are Double-Sided
Part numbers that end in SS are Single-Sided

Power Supplies

Part #	CV	Input (volts)	Output (watts)
ALLCV122120277	122-120	120-277	24
ALLCV125120	125120	120	60
ALLCV125120277	125-120	120-277	60
ALLCV12125MV	12125		60